



Application: Fish dragging, scalloping.

- Features:
- Direct planetary gear drive power in / power out
 - Variable Displacement, Piston Drive Motor
 - Two Speed (250 PSI Pilot Required For Speed Selection)
 - Automatic, Failsafe Brake
 - Standard Zinc & Epoxy Marine Finish

- Options:
- Hot dip galvanize finish
 - Diamond screw levelwind Over or Under Spooled

Specifications / Performance	
Bare Drum	23,200 lbs. @ 113 ft/min
Full Drum	8,610 lbs. @ 305 ft/min
Drum Size	16" dia. barrel, 48" dia. flanges x 16.0" to 28.5" wide
Hydraulic Requirements	Normal: 46 GPM @ 3,000 PSI / Maximum: 52 GPM @ 3,000 PSI

Performance shown for winch in low speed range. In high range, speeds are double and pulls are half.

Drum Capacity in Fathoms					
Winch Model	Drum Width	Wire Diameter			
		9/16"	5/8"	3/4"	7/8"
HGDB-1648	16.0"	900	750	500	390
HGDB-1948	19.1"	1,075	900	575	450
HGDB-2248	22.3"	1,250	1,075	675	525
HGDB-2548	25.4"	1,425	1,200	775	620
HGDB-2848	28.5"	1,600	1,365	875	685