



Application: Fishing, scalloping, anchor.

- Features:
- Totally enclosed oil bath drive
 - Standard 6000 Series motor
 - Heavy duty spindle band brake
 - Machined jaw clutch
 - Rolling element bearings
 - Heavy duty HSDF main shaft
 - Standard zinc & epoxy marine finish
- Options:
- Hot dip galvanize finish
 - Mounted & prepped controls
 - Warping head
 - Auto Spooling
 - Hydraulic brake

Specifications / Performance	
Bare Drum	11,000 lbs. @ 80 ft/min
Full Drum	3,100 lbs. @ 284 ft/min
Drum Size	6-5/8" dia. barrel, 26" dia. flanges x 10" to 22" wide
Hydraulic Requirements	24 GPM @ 2,500 PSI

Drum Capacity in Fathoms									
Winch Model	Drum Width	Wire Diameter							
		3/8"	7/16"	1/2"	9/16"	5/8"	3/4"	7/8"	1"
HSF-1026	10"	315	240	185	150	120	85	60	50
HSF-1226	12"	380	290	225	180	145	105	75	60
HSF-1426	14"	440	340	260	210	170	120	90	70
HSF-1626	16"	500	385	300	240	190	140	100	80
HSF-1826	18"	570	435	340	270	220	160	110	90
HSF-2026	20"	630	480	375	300	240	175	125	95
HSF-2226	22"	695	530	410	330	265	190	140	105