



Application: Fishing, scalloping, anchor.

- Features:
- Totally enclosed oil bath drive
 - Choice of geroller or radial piston motor
 - Oversized heavy duty manual band brake
 - Machined 3-jaw dog clutch
 - Rolling element bearings
 - Standard epoxy marine finish

ISO 9001
REGISTERED

- Options:
- Hot dip galvanize finish
 - Mounted & prepiped controls
 - Warping head
 - Diamond screw levelwind

Specifications / Performance	
Bare Drum	15,000 lbs. @ 100 ft/min
Full Drum	4,280 lbs. @ 350 ft/min
Drum Size	8-5/8" dia. Barrel, 34" dia. flanges x 14" to 22" wide
Hydraulic Requirements	35 GPM @ 2,700 PSI

Drum Capacity in Fathoms									
Winch Model	Drum Width	Wire Diameter							
		3/8"	7/16"	1/2"	9/16"	5/8"	3/4"	7/8"	1"
HSF-1434	14"	950	700	540	425	345	240	175	135
HSF-1634	16"	1,085	800	620	485	390	275	200	155
HSF-1834	18"	1,220	900	695	550	445	310	225	175
HSF-2034	20"	1,350	1,000	770	600	495	340	250	190
HSF-2234	22"	1,490	1,100	850	670	540	375	275	210